


Rittal – The System.

Faster – better – everywhere.

Top Therm Filter Fans



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

**More pressure.
Higher air flow rates.**



Installation without tools

- Snap-in mounting for easy installation
- Simple reversal of the air flow direction by turning the fan module
- Flexible positioning of the power connection
- Spring clamp terminals for electrical connection without tools
- Louvered grille latch for fast filter mat replacement without tools

Efficient technology

- Air throughput from 12 - 530 cfm (20 to 900 m³/h)
- New diagonal fan technology for greater pressure stability and constant air flow when installed, even with a contaminated filter mat
- Reduced installation depth
- Flow-optimized air routing
- Extended service life of filter mats and thus longer maintenance intervals
- UL Type 12 (IP 54) out of the box
- All fan models available with EMC shielding

Air routing

- Intelligent combination of radial and axial fan technology for most fan models
- Air flow spreads diagonally from the fan, promoting even air distribution throughout the enclosure

Additional environmental protection

- Hose-proof hoods prevent the entry of water
- Ratings of up to UL Type 4X are achieved with addition of hood

