

High-speed, noiseless thermal printer incorporates the latest in thermal array printheads and microprocessor technology. Selectable functions include baud rates, fonts, print direction and black or white print. RS232/20mA input models

- 6710** – 20 columns
- 6714** – 40 columns

**PROGRAMMABLE FEATURES**

- Time interval<sup>1</sup> - establishes a specific time interval (from 1 second to 24 hours) between printing sequences
- Interval print program<sup>1</sup> - Implements a pre-programmed series of commands. Typical commands include time/date headers, different type size, and programmed messages
- Synchronization time<sup>1</sup> - Begins the interval print program at a specific time of the day
- Character program<sup>2</sup> - Allows the 6700 to communicate with data sources. The program establishes a sequence of up to 20 characters and executes a pre-programmed print routine after these characters have been received a designated number of times
- Printer ID<sup>2</sup> - Enables each printer to be individually addressed
- User messages<sup>2</sup> - Creates up to 64 printable messages, each up to 32 characters long
- User programs<sup>2</sup> - Defines up to 32 individual command sequences, each up to 64 characters long, which are implemented on demand using an assigned program number
- Lockout code<sup>1,2</sup> - Eliminates unauthorized changes to the printer setup data

**NOTES:**

- <sup>1</sup>Available only with Clock Option K
- <sup>2</sup>Available only with 2K Buffer Option M

<i>MODEL NUMBER &gt;&gt;&gt;&gt;&gt;&gt;</i>	<b>67</b>	
	Model	
RS-232/20mA (20 Columns)	10	
RS-232/20mA (40 Columns)	14	
	Options	
Switch Setable Clock (battery pack)		K
24 Byte buffer with messages, print program and printer ID (battery backed)		M
24 VDC Excitation Supply		P
230 VAC Powered		S
Accessories:		
19-24388 Thermal paper-24 rolls/case		



Panel Mount Printers

- Excellent print quality
- 7 lines per second print speed
- High resolution – 6 dots/mm (320 dots/line)
- Printhead life – greater than 5 million lines
- Works with “clean room paper”
- Noiseless printing
- Easy paper loading
- 80 character buffer
- Selectable print character via front panel
- Selectable baud rate from 75 to 9600
- Word wrap, complete word printing
- Unique “help” command assists with setup and data entry
- Dimensions: 2.75"H x 6.31"W x 9.25"D (69.9 x 160.3 x 235.0mm)  
Panel cutout: 2.68"H x 5.44"W (68 x 138mm)
- 115/230VAC operation

Printers // 6700 Series



6600



6800

Panel Mount and Desktop Printers

**6800 Series:** A compact, *inexpensive* Desktop thermal printer that is ideal for clean room, data logging, message printing and data recording applications or recording operations wherever hard copy is needed.

Buffered input types permits interface with virtually all computer-based equipment and instrumentation.

STANDARD FEATURES

- Quiet and reliable thermal printhead
- 21 column (with selectable 40 column font)
- 2 line buffer
- Print speed of greater than 1.2 lines/second
- Easy paper load
- Works with "clean room paper"
- Compact size  
3"H x 6"W x 7" D  
(76.2 x 152.4 x 177.8mm)
- 115/230VAC powered

**Panel Mounted 6600A Series:** Microprocessor-based 16-40 column dot matrix impact printers offer a wide variety of buffered input types and data rates to simplify interface with panel meters and other digital equipment.

STANDARD FEATURES

- Switch-Selectable word wrap converts long lines of data to a readable format without hyphenating words or splitting numbers
- Plain paper design for crisp text and reduced cost
- Standard two- to four-line buffer  
2K character nonvolatile buffer optional
- Data entry via front panel keypad
- 5 x 7 dot matrix impact print can be switched to tall (5 x 14), wide (10 x 7) and bold (10 x 14)
- Print speed: 42 lines per minute
- Compact: 2.87" (72.9mm) H x 5.7" (144.88mm) W x 9.25" (235mm) D. Cutout: 2.78" (70.6mm) H x 4.5" (114.3mm)W
- *Optional* battery-backed real-time clock

MODEL NUMBER >>>>>>	661		
	Model		
	24 Columns	0	
	32 Columns	2	
	40 Columns	4	
	Options*		
	110 VAC Powered		P
	9-35 VDC Powered		R
	Clock Option		K
	2K BYTE Buffer		M
*NOTE: Without the P or R in model number, unit is 5 VDC Powered			
Accessories:			
19-22028	24 Paper Rolls and 12 BLUE Ribbons		
19-22459	24 Paper Rolls and 12 BLACK Ribbons		

MODEL NUMBER >>>>>>	68		
	Model		
	RS-232/20mA (6470 Compatible)	70	
	Options		
	Switch Setable Clock		K
	24 Buffer		M
Accessories:			
19-24679	Thermal paper, Black Image – 24 rolls/case		

Printers // 6600A/6800 Series